



P R E F O R M E D		
Stainless Steel		
T Y P E 316		
Diameter (Inches)	Breaking Strength Pounds	Weight lbs per foot
1 x 19		
-	-	-
1/16"	-	-
3/32"	1150	20.0
1/8"	1780	35.0
5/32"	2800	55.0
3/16"	4000	77.0
7/32"	6350	102.0
1/4"	6900	135.0
9/32"	9400	170.0
5/16"	10600	210.0
3/8"	14800	300.0
7/16"	20000	410.0
1/2"	27000	521.0
9/16"	32400	670.0
5/8"	42000	855.0

20%




1 x 19

Designed primarily for standing rigging on medium and large size boats. (left hand lay only)




7 x 19

The most flexible of marine cables. High strength and resistance to crushing loads. Used for guys, halyards, running backstays, topping lifts and wire sheets.



7 x 7

The standard flexible cable. Used primarily on small boats for standing rigging where flexibility is required.



WHITE VINYL COATED

Commonly used for handrails and life lines. Outside diameter of coating same as shank diameter of swaged fittings.

Stainless Steel		T Y P E	
WHITE VINYL COATED		302	
Bare Cable	Vinyl Outer Diameter	Breaking Strength Pounds	Weight Pounds M Feet
7 x 7			
1/16"	1/8"	480	13.5
1/8"	7/32"	1700	41.0
1/8"	1/4"	1700	45.0
3/16"	1/4"	3700	80.0
3/16"	5/16"	3700	92.0
1/4"	3/8"	6100	145.0

Hunter Marine Standing rigging is made from 1 x 19 x 316 wire. Standing rigging tensions are 20 % of the wires breaking strength. Life lines are 7 x 7 PVC coated.